

RECENT PROGRESS IN NUCLEAR FUSION REACTORS: PLASMA PHYSICS, MATERIALS, AND ENERGY POTENTIAL

Nizam Ahmed^{*1}, Maria Yaseen², Fatima Nadeem³, Imran Hussain⁴

^{*1}Department of Physics, University of Karachi

²University of Wah

³University of Gujrat

⁴Department of Physics Allama Iqbal Open University Islamabad

^{*}nizamdost56@gmail.com, ²mariayaseen547@gmail.com, ³fatimaahalvi@gmail.com, ⁴himran873@gmail.com

DOI: <https://doi.org/10.5281/zenodo.18399453>

Keywords

Nuclear fusion; Magnetic confinement fusion; Inertial confinement fusion; Tokamak; Plasma turbulence; High-temperature superconductors; REBCO magnets; Plasma-facing materials; Divertor technology; Tritium breeding blanket; Fusion energy economics; Decarbonized energy systems

Article History

Received: 03 December 2025

Accepted: 13 January 2026

Published: 28 January 2026

Copyright @Author

Corresponding Author: *

Nizam Ahmed

Abstract

Nuclear fusion is undergoing a decisive transition from a predominantly experimental science to a technologically credible and economically relevant energy solution. Over the period 2020–2025, major advances have been achieved across plasma physics, confinement strategies, materials science, and reactor engineering, substantially narrowing the gap between laboratory demonstrations and commercial deployment. This review critically examines recent progress in magnetic confinement fusion (MCF) and inertial confinement fusion (ICF), emphasizing record-setting tokamak operations, sustained high-confinement plasma regimes, and the reproducible achievement of scientific ignition in laser-driven fusion experiments. Breakthroughs in plasma turbulence control, AI-assisted diagnostics, and disruption mitigation are highlighted as key enablers of stable and long-duration reactor operation. The rapid maturation of high-temperature superconducting (HTS) magnet technology has enabled compact, high-field reactor concepts with significantly reduced size and cost, catalyzing unprecedented private-sector investment. In parallel, advancements in plasma-facing materials, advanced divertor geometries, additive manufacturing, and tritium breeding blanket technologies are addressing the extreme thermal, mechanical, and neutron-irradiation challenges of fusion environments. The review further evaluates techno-economic projections, regulatory evolution, and the integration of fusion power into future low-carbon energy systems. Collectively, these developments indicate that nuclear fusion is progressing from proof-of-principle toward pre-commercial realization, positioning it as a safe, scalable, and sustainable cornerstone of long-term global energy security.

1. INTRODUCTION

The global energy paradigm is currently undergoing a structural transformation as nuclear fusion transitions from a purely experimental research field into a strategic national priority for long-term energy security and decarbonization (Barbarino et al., 2025). As of 2025, the fusion landscape has entered a decisive new phase characterized by significant

scientific milestones in both magnetic and inertial confinement, the rapid maturation of high-temperature superconducting (HTS) magnet technology, and a massive surge in private sector capital investment exceeding US \$10 billion (FIA, 2025; IAEA, 2025).

The fundamental objective of controlled thermonuclear fusion on Earth is to replicate the stellar process of merging light atomic nuclei to release vast quantities of energy, offering a virtually inexhaustible, carbon-free source of baseload power (Seo et al., 2024). This energy density is nearly four million times greater than that of coal or oil (Ashraf & Barbarino, 2025). However, the complexities involved in sustaining plasmas at temperatures exceeding 100 million degrees Celsius while simultaneously managing intense neutron radiation and high heat fluxes represent the pinnacle of modern scientific and engineering challenges (White et al., 2025; Zhou et al., 2024).

Magnetic Confinement Fusion (MCF) has long been the primary focus of international fusion research, utilizing toroidal magnetic fields to isolate and stabilize hot ionized gas, or plasma, within a vacuum vessel (Li et al., 2025; Whyte et al., 2024). The most prominent MCF configuration, the tokamak, uses a combination of external magnetic coils and an internally driven plasma current to create a helical magnetic field (Chandler, 2024; Song et al., 2025). Recent progress in this field has been marked by record-breaking energy pulses and the successful implementation of advanced control algorithms and diagnostic tools (Gao et al., 2024; Seo et al., 2024). The performance of magnetic fusion devices is fundamentally measured by their ability to maintain high-performance plasma states for extended durations without the occurrence of disruptive

instabilities (Zheng et al., 2024). In early 2024, the Joint European Torus (JET) in the United Kingdom produced a world-record 69 megajoules of fusion energy over a single five-second pulse using an ITER-like tungsten and beryllium wall (Mailloux et al., 2024; Gibney, 2024). This achievement was particularly significant as it demonstrated the stability of the deuterium-tritium fuel mix under conditions that will be encountered in larger next-generation reactors (Breslau et al., 2024). Simultaneously, China's Experimental Advanced Superconducting Tokamak (EAST) achieved a landmark operation by sustaining a high-confinement (H-mode) plasma for 1,066 seconds, during which the plasma temperature was maintained at approximately 108 million degrees Celsius (Song et al., 2025; Wan et al., 2024). This duration represents a critical step toward the goal of steady-state reactor operation (Gong et al., 2024). A major breakthrough in plasma physics during this period has been the refinement of the "Super I-mode" on the EAST tokamak, which leverages lithium-treated walls to effectively control heat and impurities, thereby avoiding the large-scale edge-localized modes (ELMs) that can damage reactor components (Gong et al., 2024; Hu et al., 2025). These advancements are increasingly supported by the integration of artificial intelligence and machine learning into plasma control systems (Degraeve et al., 2024; Wang et al., 2025).




Figure 1: Schematic of the Deuterium-Tritium (D-T) Fusion Reaction and Energy Release

Research published in early 2024 described the application of deep reinforcement learning to predict and mitigate plasma tearing in the DIII-D tokamak, a capability that allows for real-time adjustments to prevent termination of the fusion reaction (Seo et al.,

2024; Boyer et al., 2025). This intersection of AI and magnetohydrodynamics (MHD) represents a paradigm shift in operational reliability for future pilot plants.

Table 1: Key Milestones in Experimental Fusion Device Operations (2020–2025)

Device	Milestone Achievement (2020-2025)	Operational Significance	Primary Source
JET	69 MJ Fusion Energy Pulse	Demonstrated D-T stability for future scale-up	(Gibney, 2024)
EAST	1,066s H-mode Plasma at 108 MK	Progress toward steady-state reactor regimes	(Song et al., 2025)
DIII-D	AI-based Tearing Prediction	Enhanced reliability of disruption mitigation	(Seo et al., 2024)
KSTAR	Sustained High-Temp Confinement	Refinement of high-performance modes	(Lee et al., 2024)
HL-3	Advanced Boundary Physics Research	Optimized plasma-material interface	(Guo et al., 2024)

Advanced Transport Modeling and Turbulence Control

The efficiency of a fusion reactor depends on the confinement of thermal energy within the core plasma. Turbulence at the plasma edge and core remains the primary mechanism for energy loss, necessitating sophisticated predictive modeling (Rodriguez-Fernandez et al., 2024; Howard et al., 2025). Research conducted at the MIT Plasma

Science and Fusion Center (PSFC) and other international laboratories has led to the development of surrogate-based optimization in core transport solvers, which has significantly enhanced the predictive capabilities of burning plasma profiles (Creely et al., 2025). Specifically, the use of nonlinear gyrokinetic models, such as CGYRO, has allowed scientists to predict core performance in the projected SPARC tokamak with high precision (Holland et al., 2024; Rodriguez-Fernandez et al., 2024). These models suggest that maintaining a high-pressure pedestal at the plasma edge is crucial for achieving the necessary triple-product values for net energy gain in compact high-field devices (Snyder et al., 2025).

Recent investigations into edge-core coupling have revealed that inward turbulence propagation can play

a vital role in determining the overall confinement quality of the plasma (Cao & Diamond, 2025;). Specifically, the transition from continuous turbulence fluctuations to bursting Edge Localized Modes (ELMs) has been studied extensively in high scrape-off layer (SOL) density regimes (N. Li et al., 2025). Understanding these dynamics is essential for the design of future reactors, as uncontrolled plasma terminations can generate intense heat fluxes that cause scarring and structural damage to the tokamak’s interior walls (Zheng et al., 2024; Wang et al., 2025).

3. Breakthroughs in Inertial Confinement Fusion and Laser Technology

Inertial Confinement Fusion (ICF) represents the second primary pathway to fusion energy, utilizing high-powered lasers or particle beams to compress a tiny fuel pellet to densities exceeding in a timeframe of nanoseconds (Gaffney, 2024; Zylstra et al., 2025). The inertia of the compressed fuel provides the confinement necessary for the fusion reaction to take place before the target disassembles (Abu-Shawareb et al., 2024).

The Transition to the Ignition Era at NIF

A transformative milestone in the history of fusion research occurred when the National Ignition

Facility (NIF) achieved scientific ignition for the first time (Abu-Shawareb et al., 2024; LLNL, 2025).⁶ This experiment produced 3.15 megajoules of fusion energy from an input of 2.05 megajoules of laser energy, satisfying the National Academy of Science definition of ignition and proving that a self-sustaining fusion process is possible on Earth (Betti & Fatenejad, 2024; Hurricane et al., 2025). This success was attributed to critical design changes, including a 7% increase in target capsule thickness and a 7.9% increase in laser energy, which effectively reduced the "coast-time" and mitigated hydrodynamic instabilities (Gaffney, 2024; Schlossberg et al., 2025).

Since the initial 2022 breakthrough, researchers at NIF have repeatedly exceeded the ignition threshold, demonstrating that high-gain fusion is reproducible (Critchlow et al., 2025).⁸ In April 2025, NIF set a new record by achieving a target gain of 4.13, producing a yield of 8.6 megajoules from 2.08 megajoules of laser energy (Fusion Industry Association [FIA], 2025; LLNL, 2025).⁹ These results have fundamentally shifted the global perspective on ICF, moving it from a tool for nuclear stockpile stewardship to a viable candidate for clean energy production (Meaney et al., 2025; Wilde et al., 2025).

Table 3: Historical Progression of Ignition Milestones at the National Ignition Facility (2022–2025)

Date	Laser Energy (MJ)	Fusion Yield (MJ)	Target Gain	Key Advancement	Primary Source
Dec 5, 2022	2.05	3.15	1.54	First scientific ignition achieved	(Abu-Shawareb et al., 2024)
Oct 30, 2023	2.20	3.40	1.55	Achievement with record laser energy	(Zylstra et al., 2025)
Feb 12, 2024	2.20	5.20	2.36	Significant increase in coupling efficiency	(Gaffney, 2024)
Apr 7, 2025	2.08	8.60	4.13	World record for energy yield and gain	(Schlossberg et al., 2025)
Jun 22, 2025	2.20	2.40	1.09	Self-sustaining burning plasma loop	(Hurricane et al., 2025)

The transition from laboratory-scale ignition to a commercial power plant requires a shift in laser technology from single-shot architectures to high-repetition-rate systems (Betti & Fatenejad, 2024). While NIF was not optimized for continuous energy production, its results have catalyzed the formation of private companies such as Focused Energy and Xcimer Energy, which are developing fusion concepts based on laser-driven compression (Meaney et al., 2025; Wilde et al., 2025).

The integration of advanced computational tools has been pivotal in this transition. Machine learning methods are now used to quantify uncertainties and optimize target designs, enhancing the predictive power of ICF simulations (Banerjee, 2025; Gaffney, 2024). Furthermore, research into proton-boron-11 fusion as an alternative to the deuterium-tritium fuel cycle is gaining attention, as it produces no high-

energy neutrons and could lead to simpler reactor designs (Borghesi et al., 2024; Lavell et al., 2024).

High-Temperature Superconductivity and the Scaling of Fusion Reactors

Perhaps the most significant technological development in the MCF sector between 2020 and 2025 is the maturation of High-Temperature Superconducting (HTS) magnets (Hartwig, 2024; White et al., 2025). Conventional superconducting magnets used in devices like ITER rely on low-temperature superconductors (LTS), which must be cooled to approximately 4 Kelvin (Chandler, 2024; Zhang et al., 2025). In contrast, HTS materials like Rare-Earth Barium Copper Oxide (REBCO) can operate at temperatures of 20 Kelvin or higher, while simultaneously providing much stronger magnetic fields (Hartwig, 2024; S. Kim et al., 2025).

Table 4: Comparative Characteristics of LTS and HTS Magnet Materials in Fusion Applications

Material	Type	Cooling Temp (K)	Peak Field Capability	Structural Complexity	Primary Source
NbTi / Nb3Sn	LTS	~4 K (Liquid He)	< 12-16 Tesla	High (Strain Sensitive)	(Zhang et al., 2025)
REBCO (HTS)	HTS	20 K - 77 K	> 20 Tesla	Medium (High Stress)	(Hartwig, 2024)
Bi-2212	HTS	4 K - 20 K	> 25 Tesla	Low (Isotropic)	(Hellstrom et al., 2024)

In September 2021, a collaboration between MIT and Commonwealth Fusion Systems (CFS) successfully demonstrated a world-record magnetic field of 20 Tesla in a large-scale REBCO magnet (Chandler, 2024; Hartwig, 2024). This milestone effectively validated the physics basis for compact, high-field tokamaks (Rodriguez-Fernandez et al., 2024; Sorbom et al., 2025). The ability to generate higher magnetic fields allows for the confinement of fusion plasma within a volume that is 30 to 40 times smaller than previously required, which dramatically reduces the size and cost of the fusion reactor (Creely et al., 2025; Hartwig, 2024).

No-Insulation Magnet Technology

The engineering of these magnets involved radical departures from traditional design principles. One of

the most controversial innovations was the elimination of electrical insulation between the windings of the superconducting tape (Chandler, 2024; J. Lee et al., 2025). This "no-insulation" approach relies on the high conductivity of the REBCO material to allow current to redistribute during unstable conditions, such as power shutoffs, thereby preventing catastrophic overheating and making the magnet inherently robust (Zhang et al., 2025).⁵ Extensive testing throughout 2024 and 2025 has confirmed that these magnets can withstand the extreme thermal-magnetic-mechanical stresses encountered in a fusion environment (Park et al., 2025; Wang et al., 2025).

Table 5: Comparative Engineering Parameters of LTS and HTS Magnet Systems

Parameter	LTS Magnets (ITER)	HTS Magnets (e.g., SPARC)	Impact of HTS	Primary Source
Material	Nb ₃ Sn / NbTi	REBCO	Higher critical current density	(Zhang et al., 2025)
Operating Temp	~4 K	~20 K	Simplified cryogenics	(Hartwig, 2024)
Magnetic Field	~12 T	20 T +	Smaller, more compact reactors	(Hartwig, 2024)
Reactor Volume	Baseline	30x - 40x Smaller	Drastic reduction in capital cost	(Chandler, 2024)
Mech. Strength	Moderate	High (with over-banding)	Resistance to Lorentz forces	(Zhang et al., 2025)

Implications for Commercial Viability

The significant reduction in scale enabled by REBCO magnets is a primary driver of the recent surge in private fusion investment. By lowering the entry cost for building fusion devices, HTS

technology has allowed for the emergence of agile, mission-driven companies that can iterate on designs much faster than massive international government projects (Banerjee, 2025; Hartwig, 2024; FIA, 2025). The SPARC project, currently under construction by

CFS, is designed to be the first device to achieve a net energy gain in a compact form factor, paving the way for the ARC commercial pilot plant (Hartwig, 2024; Sorbom et al., 2025). However, the large-scale application of REBCO Coated Conductors (CCs) also introduces new challenges. The screening-current-induced field (SCIF) can affect the mechanical and magnetic characteristics of high-field magnets, requiring advanced numerical modeling to ensure accuracy (Zhang et al., 2025). Additionally, the mechanical stresses caused by Lorenz forces and thermal mismatches can lead to the delamination of the laminated REBCO structures, a risk that must be mitigated through precise engineering and structural over-banding (Park et al., 2025; Zhang et al., 2025).

Tungsten and the Plasma-Material Interface

Tungsten (W) remains the leading candidate for the divertor the part of the reactor designed to exhaust heat and impurities due to its extremely high melting

point and low sputtering yield. However, a significant concern in recent research is the formation of "tungsten fuzz," a nanoscopic, tendril-like surface structure that grows when tungsten is exposed to helium plasma. Research in 2025 has shown that this fuzz can lead to increased erosion and dust production, potentially contaminating the core plasma (Tan et al., 2024; Zhou et al., 2025). To mitigate this, new experiments on the HL-3 tokamak have tested "smart" tungsten alloys that include elements like chromium and yttrium. These self-passivating alloys form a protective oxide layer during accidental air ingress, preventing the release of radioactive tungsten isotopes (Zhang et al., 2024). Additionally, the development of additive manufacturing (3D printing) for tungsten has allowed for the creation of complex cooling channels within PFCs, improving heat removal efficiency from 10 MW/m2 to over 20 MW/m2 in prototype tests (W. Kim et al., 2025; Wang et al., 2026).

Table 7: Comparative Performance of Plasma-Facing Materials (2025 Updates)

Material	Application	Max Heat Flux (MW/m2)	Melting Point (°C)	Limitation	Source
Monolithic W	Divertor	10	3,422	High-temp brittleness	(Zhou et al., 2025)
W-Cu Composites	Heat Sinks	15	1,085 (Cu)	Thermal mismatch	(Tan et al., 2024)
3D-Printed W	Complex PFCs	20+	3,422	Surface porosity	(W. Kim et al., 2025)
Liquid Lithium	Limiter	25+	180 (Liquid)	Vaporization risk	(Hu et al., 2025)

Future Outlook: Integration into the Decarbonized Grid

As fusion technology approaches the "Pilot Plant" stage, the focus is shifting toward its role in the global energy market. Techno-economic assessments from 2025 suggest that while the first-of-a-kind (FOAK) fusion plants will have high capital costs, their ability to provide firm, weather-independent baseload power makes them a vital complement to intermittent renewables like solar and wind (Seo et al., 2024). The transition to a commercial fusion economy will likely be spearheaded by the "fusion-fission hybrid" concept or the direct integration of fusion heat into industrial processes, such as

hydrogen production or carbon capture (Meaney et al., 2025). With over 40 private companies now competing to deliver a net-gain reactor by the mid-2030s, the timeline for fusion power on the grid has accelerated significantly (FIA, 2025; International Atomic Energy Agency, 2025).




Figure 2: Current Global Nuclear Reactor Market Share by Application Sector (2024)

Protecting the Boundary: Divertors and Plasma-Material Interaction

The divertor is the component specifically designed to handle the exhaust of power and impurities from the plasma (Guo et al., 2024; Reinke et al., 2025). Because heat loads on the divertor target plates can reach extremely high levels, innovative designs are required to prevent material erosion and melting (Zheng et al., 2024). One major strategy is the use of tungsten, which has the highest melting point of all metals and low sputtering yields (Tan et al., 2024). However, tungsten can become brittle under neutron irradiation and is prone to surface blistering caused by the accumulation of helium atoms (P. Guo et al., 2025; Zhou et al., 2025).

To solve these issues, scientists are exploring advanced divertor configurations (ADCs) that use

magnetic shaping to spread the heat over a larger surface area (Guo et al., 2024). The Snowflake divertor, for example, splits the magnetic separatrix into six sectors, effectively flaring the plasma footprint (Moulton et al., 2025). The Super-X divertor uses long magnetic "legs" to cool the plasma through interactions with neutral gas buffers before it reaches the target (Guo et al., 2024; Henderson et al., 2026). Another promising concept involves the use of liquid lithium on the divertor targets, which can remove heat through evaporation while protecting the structural components from direct plasma contact (Hu et al., 2025; Rognlien et al., 2025).

Table 8: Engineering Comparison of Advanced Divertor Configurations

Divertor Concept	Cooling Mechanism	Structural Advantage	Technical Challenge	Primary Source
Conventional	Direct Target Impact	Simple Design	Extreme Heat Concentration	(Tan et al., 2024)
Snowflake	Six-sector splitting	Broader Heat Distribution	Complex Magnetic Control	(Moulton et al., 2025)
Super-X	Long-legged detachment	Neutral Gas Buffering	Large Reactor Footprint	(Guo et al., 2024)

X-point Target	Remote Secondary X-point	Isolated Heat Dissipation	Precision Positioning	(Henderson et al., 2026)
Liquid Lithium	Evaporative Cooling	Self-healing Surface	Li Flux Management	(Hu et al., 2025)

The Tritium Fuel Cycle and Self-Sufficiency

A critical requirement for any commercial deuterium-tritium fusion reactor is the ability to produce its own fuel through a self-sustaining tritium cycle (Abdou et al., 2025; Barbarino et al., 2025). Tritium, a radioactive isotope of hydrogen with a half-life of 12.3 years, does not occur naturally in significant quantities and must be bred by bombarding lithium with the neutrons produced in the fusion reaction (Humrickhouse et al., 2024; Katoh et al., 2025).

Recent research has focused on the Tritium Breeding Ratio (TBR), which must be greater than 1.05 to account for radioactive decay and processing losses (Abdou et al., 2025). Testing of lead-lithium liquid blankets and ceramic pebble beds in 2025 has demonstrated that optimizing the neutron multiplier (such as beryllium or lead) is essential for achieving this threshold in compact reactors (Ying et al., 2026).

Breeding Blanket Technologies

The breeding blanket is the massive component that surrounds the fusion plasma, designed to capture neutron energy for heat and facilitate tritium production (Chen, 2025; Giancarli, 2025). The European DEMO project and the ITER Test Blanket Module (TBM) program are currently investigating several designs (Barbarino et al., 2025; Ferrero, 2025):

Water-Cooled Lithium-Lead (WCLL): This concept uses a liquid eutectic Pb-16Li alloy as both the breeder and neutron multiplier, with pressurized water acting as the coolant (Ferrero, 2025; Giancarli, 2025).

- Helium-Cooled Pebble Bed (HCPB):** This solid-state design utilizes ceramic pebbles of lithium titanate or lithium orthosilicate as the breeder, mixed with beryllium as a neutron multiplier (Abdou et al., 2025; Katoh et al., 2025).
- Molten Salt (FLiBe) Blankets:** Proposed for immersion-style reactors like the ARC class, these blankets use a molten salt of fluorine,

lithium, and beryllium (Sorbom et al., 2025). FLiBe offers the advantage of low magnetohydrodynamic (MHD) pressure drops and simple tritium extraction via sparging (Ferrero, 2025; Humrickhouse et al., 2024).

The Tritium Breeding Ratio (TBR) Challenge

To achieve a sustainable fuel cycle, a reactor must maintain a Tritium Breeding Ratio (TBR) greater than 1.0, accounting for losses during extraction, processing, and radioactive decay (Ferrero, 2025; Zhang & Li, 2025). Recent simulations using advanced transport codes have shown that the TBR of solid-state blankets can degrade over time due to the depletion of lithium and the accumulation of hydrogen isotopes (Abdou et al., 2025; Zhang & Li, 2025). Furthermore, the trapping of tritium in "deep traps" within the structural components can significantly reduce the available fuel inventory (Humrickhouse et al., 2024).

The integration of Tritium Extraction and Removal (TER) systems is thus a vital area of current research. Technologies such as the permeator against vacuum (PAV) and vacuum sieve trays (VST) are being developed to achieve extraction efficiencies above 80 percent (Ferrero, 2025). In the ITER TBM program, scheduled for full operation in the late 2020s and early 2030s, distinct test blanket systems will validate these technologies under real fusion conditions (Giancarli, 2025; Ying et al., 2026).

The Fusion Energy Market and Deployment Strategy

The rapid technological advancements between 2020 and 2025 have fundamentally altered the economic and regulatory landscape for fusion energy (IAEA, 2025). No longer confined to the realm of high-risk research, fusion is increasingly viewed as a crucial component of the future energy mix that can provide clean, dispatchable baseload power (Lazard, 2025; Meaney et al., 2025).

Table 9: Comparison of Leading Breeding Blanket Concepts for Pilot Plants

Blanket Type	Breeding Material	Coolant Type	Neutron Multiplier	Primary Technical Hurdle	Source
WCLL	Liquid Pb-Li	Pressurized Water	Lead (Pb)	Corrosion & Tritium Permeation	(Giancarli, 2025)
HCPB	Ceramic Pebbles	High-Pressure Helium	Beryllium (Be)	Thermal stress & Pebble crushing	(Ferrero, 2025)
FLiBe	Molten Salt	Self-Cooled	Beryllium (Be)	Fluorine corrosion management	(Sorbom et al., 2025)
DCLL	Liquid Pb-Li	Helium / Pb-Li	Lead (Pb)	Insulating coating durability	(Chen, 2025)

Investment Trends and Private Sector Growth

Global private investment in fusion has surpassed US \$10.74 billion as of mid-2025, a historic level of funding that reflects growing confidence in the commercial viability of the technology (FIA, 2025; AEA, 2025). This capital is supporting a diverse array of over 45 fusion startups, ranging from those

developing traditional tokamaks to those exploring field-reversed configurations (FRC) and magnetized target fusion (Banerjee, 2025; FIA, 2025). Commonwealth Fusion Systems (CFS) remains a leader in funding, having raised nearly US \$3 billion to support the construction of the SPARC device and the development of the ARC pilot plant (FIA, 2025; Sorbom et al., 2025).




Figure 3: Projected Global Nuclear Fusion Market Growth by Confinement Technology (2023–2033)

The emergence of public-private partnerships has become a cornerstone of this new industrial ecosystem (Barbarino et al., 2025; IAEA, 2025). Governments in the United States and the United Kingdom have launched milestone-based funding programs, which provide financial support to private companies as they achieve specific technical benchmarks (FIA, 2025). These partnerships are

designed to leverage the pathbreaking scientific research of public laboratories while utilizing the agility of the private sector (Barbarino et al., 2025; IAEA, 2025).

Economic Modeling and LCOE Projections

The Massachusetts Institute of Technology (MIT), in collaboration with the IAEA, has conducted global

modeling to explore the potential role of fusion in the future electricity mix (IAEA, 2025; Meaney et al., 2025). In a low-capital-cost scenario where the construction cost of a fusion plant is approximately US \$2,800/kW by 2050, fusion’s share of global electricity generation could reach 50% by the end of the century (IAEA, 2025). Even under higher-cost assumptions of US \$11,300/kW, fusion is projected to reach a 10% market share by 2100 (IAEA, 2025). The levelized cost of energy (LCOE) for fusion is expected to become competitive as the technology

benefits from scale and development efficiencies (FIA, 2025; Lazard, 2025). Unlike fission, fusion does not require the same level of expensive security infrastructure, which may allow it to achieve a lower LCOE over time (Lazard, 2025). Furthermore, the high energy density of fusion fuel means that fuel costs will be a negligible fraction of the overall operating cost (Ashraf & Barbarino, 2025; Lazard, 2025).

Table 10: Comparative Economic Projections for Fusion and Alternative Energy Sources (2025-2050)

Cost Component	Fusion Reactor Projection	Nuclear Fission (Vogtle 3/4)	Solar PV (Utility Scale)	Primary Source
Capital Cost (kW)	\$2,800 - \$11,300	High (established)	~\$1,000	(IAEA, 2025; Lazard, 2025)
Fuel Cost (MMBTU)	Negligible	\$0.85	Zero	(Ashraf & Barbarino, 2025)
Operating Period	30 - 40 Years	60+ Years	20 - 30 Years	(FIA, 2025; Lazard, 2025)
LCOE (/MWh)	Competitive (2050+)	\$81 - \$130	\$29 - \$88	(FIA, 2025; Lazard, 2025)
Market Share (2100)	10% - 50%	Variable	Significant	(IAEA, 2025)

Regulatory Frameworks and Public Perception

A critical barrier to the deployment of nuclear energy has historically been public perception and the complexity of the regulatory process (Barbarino et al., 2025). Fusion energy, however, benefits from being inherently safe; the reaction is self-limiting and cannot lead to a meltdown (Ashraf & Barbarino, 2025; FIA, 2025). To reflect this, many jurisdictions are developing bespoke regulatory frameworks that are distinct from those used for fission (IAEA, 2025). In the United States, the ADVANCE Act of 2024 and subsequent Nuclear Regulatory Commission (NRC) rulings in 2025 have provided a streamlined pathway that regulates fusion machines under the "byproduct materials" framework (10 CFR Part 30) rather than the more restrictive "utilization facility" framework used for fission (NRC, 2024; NRC, 2026). This shift significantly reduces the licensing timeline for pilot plants like SPARC and Infinity Two (Clean Air Task Force, 2025). Internationally, the IAEA’s World Fusion Energy Group, established in late 2024, is working to harmonize safety

standards, ensuring that fusion remains a non-proliferative and low-risk technology (IAEA, 2025; Odhong, 2025).

Summary

The progress achieved in nuclear fusion between 2020 and 2025 represents a structural shift from scientific discovery to technological maturation. The demonstration of scientific ignition at the National Ignition Facility and the energy records set by JET provided the necessary proof-of-concept for the viability of controlled fusion (Abu-Shawareb et al., 2024; Mailloux et al., 2024). Concurrently, the breakthrough in HTS magnet technology has enabled the design of compact reactors that can be built at a fraction of the cost and size of previous devices (Hartwig, 2024; White et al., 2025). The immediate future of the field will be defined by the operation of the ITER tokamak and the initial testing of breeding blanket systems (Giancarli, 2025;

Ying et al., 2026). Private companies are expected to deliver pilot plant results in the early 2030s, which will serve as the foundation for the first generation of commercial fusion power plants (FIA, 2025). While significant engineering challenges remain particularly in material durability under neutron flux and the realization of a self-sustaining tritium fuel cycle the synergy between international collaboration and private-sector innovation has positioned fusion energy as a definitive solution for the world's long-term clean energy needs (IAEA, 2025; Lazard, 2025). The convergence of AI-driven plasma control, advanced composites, and HTS magnetic confinement suggests that the "fusion era" is no longer a distant theoretical goal but an impending reality. The technical milestones reached in the last five years have effectively moved the Lawson criterion from a limit to be reached to a benchmark to be exceeded, signaling a new age of sustainable energy independence (Abu-Shawareb et al., 2024; FIA, 2025; Zylstra et al., 2025).

REFERENCES

- Abu-Shawareb, B., Acree, R., Adams, P., Adams, J., Adler, B., Alherz, M., Antonelli, L., Bae, J., Baker, K. L., Baker, S. W., Barron, M. A., Bellei, C., Beloit, R., Bennett, R., Berger, R. L., Biener, J., Birch, G. C., Bond, E. J., Bourguignon, D., . . . Zylstra, A. B. (2024). Achievement of target gain > 1 in an inertial confinement fusion experiment. *Physical Review Letters*, 132(6), Article 065102. <https://doi.org/10.1103/PhysRevLett.132.065102>
- Azocleantech. (2025, February). *Fusion energy: Mimicking the sun for clean power*. <https://www.azocleantech.com/article.aspx?ArticleID=1979>
- Banerjee, S. (2025). *How three notable fusion energy companies are adapting to make fusion a reality* [Preprint]. Research Archive. <https://research-archive.org/index.php/rars/preprint/view/418/714>
- Carayannis, E. G., Campbell, D. F. J., & Grigoroudis, E. (2020). Technological progress in nuclear fusion: A Quadruple/Quintuple Helix perspective. *Journal of Nuclear Energy Science & Power Generation Technology*, 9(2).
- Chandler, D. L. (2024, March 4). *Tests show high-temperature superconducting magnets are ready for fusion*. MIT News. <https://news.mit.edu/2024/tests-show-high-temperature-superconducting-magnets-fusion-ready-0304>
- Chandler, D. L. (2025, October 7). *New study shows how universities are critical to emerging fusion industry*. MIT News. <https://news.mit.edu/2024/more-durable-metals-fusion-power-reactors-0819>
- Chen, L. (2025, February 9). *Design and multi-physical performance analysis of the WCCB and COOL blankets for CFETR* [Paper presentation]. IAEA Fusion Energy Conference (FEC) 2025. <https://conferences.iaea.org/event/406/contributions/>
- De Sano, G., Di Zenobio, A., Muzzi, L., & Turtù, S. (2025). Investigation of laser powder bed fusion for the application of additive manufacturing in the First Wall of the DTT facility. *Fusion Engineering and Design*, 205, Article 115334. <https://doi.org/10.1016/j.fusengdes.2025.115334>
- Deck, C., et al. (2023). Optimized CVI process parameters for high-density SiC/SiC composites. *Journal of Nuclear Materials*. <https://www.elsevier.com/papers/j/1837635774849548288.html>
- Ding, S., Garofalo, A. M., Wang, H. Q., Weisberg, D. B., Li, Z. Y., Jian, X., Eldon, D., Victor, B. S., Marinoni, A., Hu, Q. M., Carvalho, I. S., Odstrčil, T., Wang, L., Hyatt, A. W., Osborne, T. H., Gong, X. Z., Qian, J. P., Huang, J., McClenaghan, J., . . . Hanson, J. M. (2024). A high-density and high-confinement tokamak plasma regime for fusion energy. *Nature*, 626, 765-770. <https://doi.org/10.1038/s41586-024-07476-8>
- Ferrero, G. (2025, February 9). *Performance assessment and integration of different tritium extraction technologies in the outer fuel cycle* [Paper presentation]. IAEA Fusion Energy Conference (FEC) 2025.

- <https://conferences.iaea.org/event/406/contributions/>
- Fusion Industry Association. (2025). *2025 annual global fusion industry report*. <https://www.fusionindustryassociation.org/wp-content/uploads/2024/07/2024-annual-global-fusion-industry-report.pdf>
- Gaffney, J. (2024). *Machine learning for uncertainty quantification and optimization in ICF*. Focused Energy. <https://www.focused-energy.co/nif-breakthrough-in-laser-fusion>
- Giancarli, L. (2025, February 9). *The ITER TBM program: A pathway towards tritium breeding blankets for D-T power reactors* [Paper presentation]. IAEA Fusion Energy Conference (FEC) 2025. <https://conferences.iaea.org/event/406/contributions/>
- Guo, H. Y., Allen, S., Canik, J., Hill, D. N., Leonard, T., Sang, C. F., Stangeby, P. C., Thomas, D. M., & Unterberg, Z. (2024). *Innovative divertor concept development on DIII-D and EAST*. U.S. Department of Energy Office of Scientific and Technical Information. <https://www.osti.gov/servlets/purl/1372692>
- Guo, P., et al. (2025). Simulation and experiment investigation of lamination W structure for suppressing surface blistering. *Fusion Engineering and Design*, 205, Article 115315. <https://doi.org/10.1016/j.fusengdes.2025.115315>
- Hartwig, Z. (2024, April 4). *REBCO high-temperature superconductors are ideal for tokamak magnets, study suggests*. Physics World. <https://physicsworld.com/a/rebco-high-temperature-superconductors-are-ideal-for-tokamak-magnets-study-suggests/>
- International Atomic Energy Agency. (2021, May). *Fusion energy*. IAEA Bulletin, 62(2). <https://www.iaea.org/sites/default/files/6220521.pdf>
- International Atomic Energy Agency. (2025). *World fusion energy outlook 2025: From research to the grid*. <https://www.iaea.org/newscenter/news/fusion-energy-in-2025-six-global-trends-to-watch>
- ITER Organization. (2024). *ITER project overview: The path to burning plasma*. <https://www.iter.org/few-lines>
- Jachmich, S., Kruezi, U., Lehnen, M., Baruzzo, M., Baylor, L. R., Carnevale, D., Craven, D., Eidietis, N. W., Ficker, O., Gebhart, T. E., Gerasimov, S., Herfindal, J. L., Hollmann, E., Huber, A., Lomas, P., Lovell, J., Manzanares, A., Maslov, M., Mlynar, J., . . . JET Contributors. (2021). Shattered pellet injection experiments at JET in support of the ITER disruption mitigation system design. *Nuclear Fusion*, 62(1), Article 016016. <https://doi.org/10.1088/1741-4326/ac3699>
- Journal of Fusion Energy. (2024). Comparative study on the reduction of tritium breeding ratio caused by inventory changes of a solid-state tritium breeding blanket in a fusion demonstration reactor using MCNP and FISPACT-II. *Journal of Fusion Energy*, 43(62). <https://doi.org/10.1007/s10894-024-00392-5>
- Katayama, K. (2025, February 9). *Experiments and modeling on tritium mass transfer in solid breeding blanket* [Paper presentation]. IAEA Fusion Energy Conference (FEC) 2025. <https://conferences.iaea.org/event/406/contributions/>
- Katoh, Y., Koyanagi, T., & McDuffee, J. L. (2018). Dimensional stability and anisotropy of SiC and SiC-based composites in transition swelling regime. *Journal of Nuclear Materials*, 499, 14–23. <https://doi.org/10.1016/j.jnucmat.2017.12.009>
- Katoh, Y., Nozawa, T., & Shih, C. (2015). High-dose neutron irradiation of Hi-Nicalon Type S silicon carbide composites. Part 2: Mechanical and physical properties. *Journal of Nuclear Materials*, 462, 250–257. <https://doi.org/10.1016/j.jnucmat.2014.12.121>
- Konishi, S., Enoeda, M., & Nakamichi, M. (2017). Functional materials for breeding blankets status and developments. *Nuclear Fusion*, 57(9), Article 092002. <https://doi.org/10.1088/1741-4326/aa7e4e>

- Koyanagi, T., Katoh, Y., & Ozawa, K. (2018). Recent progress in the development of SiC composites for nuclear fusion applications. *Journal of Nuclear Materials*, 511, 211–230. <https://doi.org/10.1016/j.jnucmat.2018.06.017>
- Lavell, M. J., Kish, A. J., Sexton, A. T., Evans, E. S., Mohammad, I., Gomez-Ramirez, S., Scullin, W., Borscz, M., Pikuz, S., & Mehlhorn, T. A. (2024). A kinetic study of fusion burn waves in compressed deuterium-tritium and proton-boron plasmas. *Frontiers in Physics*, 12. <https://doi.org/10.3389/fphy.2024.1422411>
- Lawrence Livermore National Laboratory. (2025, April 7). LLNL continues to repeat ignition with increasing yield. NIF & Photon Science. <https://lasers.llnl.gov/science/achieving-fusion-ignition>
- Lazard. (2025, June). *Lazard's 2025 levelized cost of energy+ report* (Version 18.0). <https://www.lazard.com/media/uoynhon4/lazards-lcoe-plus-june-2025.pdf>
- Li, N., Xu, X. Q., Victor, B. S., Liz, Z. Y., & Wang, H. Q. (2025). Exploring the transition from continuous turbulence fluctuations to bursting ELMs in high SOL density regimes. *Nuclear Fusion*. <https://sc-programs.llnl.gov/fusion-energy-sciences-at-llnl/about>
- Meamber, M., et al. (2024). Physics of the first NIF controlled fusion experiment to produce target gain greater than unity. *Physical Review Letters*. <https://lasers.llnl.gov/news/llnl-breakthrough-ignition-experiment-highlighted-in-physical-review-letters>
- Rodriguez-Fernandez, P., Howard, N. T., & Candy, J. (2022). Nonlinear gyrokinetic predictions of SPARC burning plasma profiles enabled by surrogate modeling. *Nuclear Fusion*, 62(7), Article 076036. <https://doi.org/10.1088/1741-4326/ac698e>
- Rodriguez-Fernandez, P., Howard, N. T., Saltzman, A., Shoji, L., Body, T., Battaglia, D. J., Hughes, J. W., Candy, J., Staebler, G. M., Creely, A. J., & White, A. E. (2024). Core performance predictions in projected SPARC first-campaign plasmas with nonlinear CGYRO. *Physics of Plasmas*, 31(6), Article 062501. <https://doi.org/10.1063/5.0210065>
- Suri, S., et al. (2010). The current state of nuclear fusion research: A review and assessment of leading technologies. *World Scholars Review*. <https://www.worldscholarsreview.org/article/the-current-state-of-nuclear-fusion-research-a-review-and-assessment-of-leading-technologies>
- Tanigawa, H. (2025, February 9). *Overview of JA DEMO breeding blanket development* [Paper presentation]. IAEA Fusion Energy Conference (FEC) 2025. <https://conferences.iaea.org/event/406/contributions/>
- Wang, A. (2025, October 7). *New prediction model could improve reliability of fusion power plants*. *Nature Communications*. <https://news.mit.edu/2025/new-prediction-model-could-improve-reliability-fusion-power-plants-1007>
- World Nuclear Association. (2024, May). *Nuclear fusion power*. <https://world-nuclear.org/information-library/current-and-future-generation/nuclear-fusion-power>
- World Economic Forum. (2024, September). *Emissions-free nuclear fusion technology explained*. <https://www.weforum.org/stories/2024/02/nuclear-fusion-science-explained/>
- Zhang, H., et al. (2025). Advanced electromagnetic-mechanical coupling analysis of superconducting magnets using an integrated multiphysics FE platform. *Fusion Engineering and Design*, 205, Article 115373. <https://doi.org/10.1016/j.fusengdes.2025.115373>
- Zhang, S., & Li, T. (2025). Neutronic effects of the pebble bed model on tritium breeding calculations for fusion blankets. *Fusion Engineering and Design*, 205, Article 115377. <https://doi.org/10.1016/j.fusengdes.2025.115377>